


IGBT Modules

V_{CES} 650V
 I_c 400A

Applications

- High frequency drivers
- Solar inverters
- UPS (Uninterruptible Power Supplies)
- Electric welding machine



Features

- Low $V_{ce(sat)}$ with Trench technology
- Low switching losses
- High short circuit capability(6 μ s)
- Including ultra fast & soft recovery anti-parallel FWD
- Low inductance
- Maximum junction temperature 175°C

● IGBT

Absolute Maximum Ratings

Parameter	Symbol	Conditions	Value	Unit
Collector-Emitter Voltage	V_{CES}	$V_{GE}=0V, I_c=1mA, T_{vj}=25^\circ C$	650	V
Continuous Collector Current	I_c	$T_c=100^\circ C$	400	A
Repetitive Peak Collector Current	I_{CRM}	$t_p=1ms$	800	A
Gate-Emitter Voltage	V_{GES}	$T_{vj}=25^\circ C$	± 20	V
Total Power Dissipation	P_{tot}	$T_c=25^\circ C$ $T_{vjmax}=175^\circ C$	1250	W



Characteristic values

Parameter	Symbol	Conditions	Value			Unit		
			Min.	Typ.	Max.			
Gate-emitter Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=10.0mA, T_{vj}=25^{\circ}C$	5.0	5.7	6.6	V		
Collector-Emitter Cut-off Current	I_{CES}	$V_{CE}=650V, V_{GE}=0V, T_{vj}=25^{\circ}C$			1.0	mA		
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=400A, V_{GE}=15V, T_{vj}=25^{\circ}C$		1.70	2.0	V		
		$I_C=400A, V_{GE}=15V, T_{vj}=125^{\circ}C$		1.95				
Gate Charge	Q_G			4.60		uC		
Internal Gate Resistance	R_{gint}			0.6		Ω		
Input Capacitance	C_{ies}	$V_{CE}=25V, V_{GE}=0V,$ $f=1MHz, T_{vj}=25^{\circ}C$		37.9		nF		
Reverse Transfer Capacitance	C_{res}				0.76		nF	
Gate-Emitter leakage current	I_{GES}	$V_{CE}=0V, V_{GE}=20V, T_{vj}=25^{\circ}C$			400	nA		
Turn-on Delay Time	$t_{d(on)}$	$I_C=400A$ $V_{CE}=300V$ $V_{GE}=\pm 15V$ $R_G=1.5\Omega$ $T_{vj}=25^{\circ}C$		66		ns		
Rise Time	t_r				125		ns	
Turn-off Delay Time	$t_{d(off)}$				290		ns	
Fall Time	t_f				121		ns	
Energy Dissipation During Turn-on Time	E_{on}				6.1		mJ	
Energy Dissipation During Turn-off Time	E_{off}				8.5		mJ	
Turn-on Delay Time	$t_{d(on)}$		$I_C=400A$ $V_{CE}=300V$ $V_{GE}=\pm 15V$ $R_G=1.5\Omega$ $T_{vj}=125^{\circ}C$		80		ns	
Rise Time	t_r					157		ns
Turn-off Delay Time	$t_{d(off)}$					341		ns
Fall Time	t_f					113		ns
Energy Dissipation During Turn-on Time	E_{on}				8.3		mJ	
Energy Dissipation During Turn-off Time	E_{off}				13.2		mJ	
SC Data	I_{sc}	$t_p \leq 6\mu s, V_{GE}=15V,$ $T_{vj}=125^{\circ}C, V_{cc}=300V,$ $V_{CEM} \leq 650V$			2000		A	



● Diode

Absolute Maximum Ratings

Parameter	Symbol	Conditions	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	$T_{vj}=25^{\circ}C$	650	V
Continuous DC Forward Current	I_F		400	A
Repetitive Peak Forward Current	I_{FRM}	$t_p=1ms$	800	A





Characteristic values





Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Forward Voltage	V_F	$I_F=400A, T_{vj}=25^{\circ}C$		1.60		V
		$I_F=400A, T_{vj}=125^{\circ}C$		1.45		
Recovered Charge	Q_{rr}	$I_F=400A$		3.9		μC
Peak Reverse Recovery Current	I_{rr}	$V_R=300V$ $-di_F/dt = 4000A/\mu s$		74		A
Reverse Recovery Energy	E_{rec}	$T_{vj}=25^{\circ}C$		2.6		mJ
Recovered Charge	Q_{rr}	$I_F=400A$		10.4		μC
Peak Reverse Recovery Current	I_{rr}	$V_R=300V$ $-di_F/dt = 4000A/\mu s$		137		A
Reverse Recovery Energy	E_{rec}	$T_{vj}=125^{\circ}C$		4.9		mJ





● **Module Characteristics** $T_C=25^{\circ}\text{C}$ unless otherwise specified


Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Isolation voltage	V_{isol}	$t=1\text{min}, f=50\text{Hz}$	2500			V
Maximum Junction Temperature	T_{jmax}				175	$^{\circ}\text{C}$
Operating Junction Temperature	$T_{\text{vj op}}$		-40		150	$^{\circ}\text{C}$
Storage Temperature	T_{stg}		-40		150	$^{\circ}\text{C}$
Comparative Tracking Index	CTI		400			
Thermal Resistance Junction-to Case	$R_{\theta\text{JC}}$	per IGBT			0.12	K/W
		per Diode			0.22	
Thermal Resistance Case-to Sink	$R_{\theta\text{CS}}$	Conductive grease applied		0.012	0.035	K/W
Module Electrodes Torque	M_t	Recommended(M6)	3.0		5.0	N·m
Module-to-Sink Torque	M_s	Recommended(M6)	3.0		5.0	N·m
Weight of Module	G			315		g








● **Circuit Diagram**



● **Package Outline Information**

Dimensions in Millimeters





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.